## **EUROPEAN PATENT OFFICE**

92 " 15 " Care 2 4"

## Patent Abstracts of Japan

**PUBLICATION NUMBER** 

: 02279530

**PUBLICATION DATE** 

: 15-11-90

APPLICATION DATE

19-04-89

APPLICATION NUMBER

: 01099356

APPLICANT: NIPPON SHEET GLASS CO LTD;

INVENTOR: MIZUNO TOSHIAKI;

INT.CL.

C03B 19/12

TITLE

PRODUCTION OF PLATE-GLASS PRODUCT

ABSTRACT: PURPOSE: To easily and effectively obtain a plate glass without deformation such as warpage at the time of producing the plate glass from a raw soln. contg. an organometallic compd. by the sol-gel method means of pressing the gel in the sintering stage.

> CONSTITUTION: The plate glass is produced from a soln. contg. an organometallic compd. such as methyl orthosilicate by the sol-gel method. In this case, the gel is pressed between the pressing surfaces of two pressers when the gel is sintered to obtain the plate-glass product free of warpage. The pressure for pressing is preferably controlled to  $1\times10^2$  to  $1\times10^4$ Pa, and the pressing time is preferably controlled to 5 to 24hr. In addition, the temp. when the pressure is exerted is preferably controlled to a temp. 500°C lower than the optimum maximum temp. in the sintering stage. The plate surface is most conveniently pressed by placing a refractory weight such as firebrick on the gel.

COPYRIGHT: (C)1990,JPO&Japio